## IMPIEGO

**Tubo in gomma spiralato liscio** flessibile e robusto impiegato come collegamento per lo scarico dei WC delle imbarcazioni: prerogativa è quella **di limitare la propagazione degli odori** derivanti dal passaggio degli scarichi delle toilette. Utilizzato anche per la connessione di serbatoi biologici, pompe biologiche e pompe di sentina nelle imbarcazioni da diporto.

- ***Temperatura:*** -30° C +80° C

## STRUTTURA

- ***Sottostrato:*** liscio in gomma nera con buon livello di impermeabilità.
- ***Rinforzi:*** spirale metallica incorporata con tessuti sintetici ad alta resistenza.
- ***Copartura:*** in gomma bianca resistente all'abrasione, all'acqua di mare e agli agenti marini.
- ***Superficie:*** liscia ad impressione tela.
- ***Marcatura:*** listino scritta blu "H.T. - SANIPOMP/W - SANITATION HOSE - W.P. 7 BAR (100 PSI) - Italy"

## APPLICATION

**Hardwall smooth cover rubber hose** very flexible designed as sewage pipe for marine toilets. Its main advantage is **to limit the spreading of odours** from the toilet drains.

- ***Temperature range:*** -30° C +80° C

## CONSTRUCTION

- ***Tube:*** black, smooth. Impermeability good level rubber.
- ***Reinforcement:*** steel wire helix with high strength syntetic textile plies.
- ***Cover:*** white, abrasion, sea water and marine agents resistant rubber.
- ***Surface:*** smooth fabric finished.
- ***Branding:*** blue transfer tape lettering "H.T. - SANIPOMP/W - SANITATION HOSE - W.P. 7 BAR (100 PSI) - Italy"

| DIAMETRO INTERNO *INSIDE DIAMETER* | | DIAMETRO ESTERNO *OUTSIDE DIAMETER* | | PESO TEORICO *WEIGHT* | | PRESSIONE ESERCIZIO | | PRESSIONE SCOPPIO *BRUST PRESSURE* | | ASPIRAZIONE *VACUUM* | RAGGIO DI CURVATURA *BENDING RADIUS* | | LUNGHEZZA *LENGTH* | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| mm | inch | mm | inch | kg/mt | lbs/ft | bar | psi | bar | psi | bar | mm | inch | mt | ft |
| 16 | 5/8" | 26 | 1.1/32" | 0.56 | 0.36 | 7 | 105 | 21 | 315 | 0.9 | 65 | 2.56" | 30.5 | 100 |
| 19 | 3/4" | 29 | 1.5/32" | 0.70 | 0.47 | 7 | 105 | 21 | 315 | 0.9 | 75 | 2.95" | 30.5 | 100 |
| 25 | 1" | 35 | 1.3/8" | 0.75 | 0.50 | 7 | 105 | 21 | 315 | 0.9 | 100 | 3.94" | 30.5 | 100 |
| 38 | 1.1/2" | 48 | 1.7/8" | 1.15 | 0.77 | 7 | 105 | 21 | 315 | 0.9 | 150 | 5.91" | 30.5 | 100 |

Altri diametri e/o pressioni realizzabili su richiesta - Le caratteristiche e i dati tecnici possono essere modificati senza preavviso.
*Other diameters and/or pressures are feasible upon request - The characteristics and technical data could be changed without warning.*

Rev. 0