

Sika® Primer-206 G+P

Technical Product Data

Chemical base	Pigmented solvent based polyisocyanate solution	
Colour	Black	
Density (CQP ¹ 006-3 / ISO 2811-1)	1.05 kg/l approx.	
Viscosity ² (CQP 029-3 / ISO 3219)	10 mPas approx.	
Flash point (CQP 007-1 / ISO 13736)	-4°C approx.	
Solid content	40% approx.	
Application temperature	10°C to 35°C	
Application method	Brush or felt	
Coverage	150 ml/m ² approx.	
Flash off time ³	minimum over 15°C minimum below 15°C maximum	10 min. 30 min. 24 h
Storage	Store in sealed container in a cool dry place	
Shelf life	9 months	

¹⁾ CQP = Corporate Quality Procedure

²⁾ 23°C (73°F) / 50% r.h.

³⁾ In specific applications temperature and flash off time may be different

Industry

Description

Sika® Primer-206 G+P is a black, moisture-curing liquid primer specifically formulated for the treatment of bond faces in direct glazing work prior to application of Sika® polyurethane direct glazing adhesives.

Sika® Primer-206 G+P is manufactured in accordance with ISO 9001/14001 quality assurance system and with the responsible care program.

Areas of Application

Sika® Primer-206 G+P is used to give improved adhesion on glass and ceramic coated glass in adhesive bonding applications. Sika® Primer-206 G+P can also be used on other substrates such as plastics and some metals.

Method of Application

Surfaces must be clean, dry and free from all traces of grease, oil and dust. Wipe the bond face with Sika® Aktivator and leave to dry. Shake the can of Sika® Primer 206 G+P very thoroughly until the mixing ball is heard to rattle freely. Continue shaking for an other minute and apply a thin but covering coat with a brush or felt pad.

Do not apply at temperatures below 10°C or above 35°C. Sika® Primer-206 G+P should be applied once only. Care must be taken to ensure that this single application gives adequately dense coverage.

Reseal container tightly immediately after use.

This product is suitable for professional experienced users only. Tests with actual substrates and conditions have to be performed to ensure adhesion and material compatibility.



Important Note

Immediately after use, reseal container tightly. Prolonged exposure to atmospheric moisture will cause Sika®Primer-206 G+P to become inactive. Discard any primer that has gelled or separated.

Further Information

Copies of the following publications are available on request:

- Material Safety Data Sheets
- Sika Primer Chart

Packaging Information

Can	250 ml 1 l
-----	---------------

Value Bases

All technical data stated in this Product Data Sheet are laboratory test based. Current measured values may vary do to factors beyond our influences.

Health and Safety Information

For information and advice on the safe handling, storage and disposal of chemical products, users should refer to the most recent Material Safety Data Sheet containing physical, ecological, toxicological and other safety-related data.

Legal Notes

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users should always refer to the most recent issue of the Technical Data Sheet for the product concerned, copies of which will be supplied on request.

SVIB



Further information available at:
www.sika.co.uk
www.sika.com

Sika Limited
Industry
Watchmead, Welwyn Garden City
Hertfordshire, AL7 1BQ
United Kingdom
Tel: +44 (0)1707 394444
Fax: +44 (0)1707 329129

